

HDRB-RZRPROR-SB | HDRB-RZRPROR-01

HD RADIUS BARS FOR THE POLARIS RZR PRO R

HL

HIGHLIFTER

SEIZMIK™



✉ sales@highlifter.com
☎ 800-699-0947 | 8:00am - 5:00pm CST
📍 7455 Atkinson Drive, Shreveport, LA 71129



www.highlifter.com

Parts Available For These Popular Brands and Others

POLARIS

can-am



HONDA

Kawasaki



PRODUCT DISCLAIMER

The installation of products sold or manufactured by High Lifter Products including, but not limited to suspension components such as lift kits, gear reduction lifts, frame stiffener kits, snorkels, and tires that exceed the original specifications for the vehicle, may change the vehicle's center of gravity and handling characteristics both on- and off-road. You are aware that the installation of tires that are larger than original vehicle specifications may reduce the effectiveness of the braking system. Use of these products may place added stress to the original factory vehicle components which could cause them to weaken or possibly fail.

Products sold or manufactured by High Lifter Products are intended for off-road use only. Operation of a vehicle modified with these products on a road could result in serious bodily injury or death, and such operation may violate the laws of your state or municipality. You agree to operate your vehicle exclusively in the manner intended by the vehicle manufacturer. You agree that failure to safely and reasonably operate your vehicle could result in serious bodily injury or death, and that, as a result of installation of this product(s) to your vehicle, extreme care must be taken to prevent vehicle rollover or loss of control, which may be more likely to occur as a result of said modifications. You will avoid unsafe maneuvers, including sudden sharp turns or other abrupt maneuvers, which could make a vehicular accident more likely. You understand that High Lifter Products is not responsible or liable for any damages or any injuries to yourself or your passengers that could occur upon possible accidents due to driver error, incorrect installations, bad judgment, incompatibility with other aftermarket accessories or natural disasters to the fullest extent allowable by law.

You will have all vehicle occupants fasten seatbelts, if equipped, and wear proper safety equipment, such as DOT approved helmet and eye protection prior to operating the vehicle. You understand and acknowledge that failure to wear proper safety equipment may increase the risk of serious bodily injury or death to yourself and any passengers.

Proper installation of products sold or manufactured by High Lifter Products requires knowledge of the factory recommended procedures for removal and installation of original equipment components. Installation of these products without proper knowledge and experience may affect the performance of these components and the safety of the vehicle and cause serious bodily injury or death. It is strongly recommended that a certified mechanic familiar with the installation of similar components perform the product(s) installation.

Prior to installing any products sold or manufactured by High Lifter Products you will perform or cause to be performed an inspection of their vehicle to confirm its condition is suitable for the installation of these products. A proper inspection of the vehicle includes confirmation that the vehicle has not been in a collision and is free of corrosion. If the vehicle is suspected to have been in a collision or misused, or is otherwise unsuitable for modification, you will not install the product(s). You will continue to inspect the vehicle prior to each use to confirm its condition is suitable for its intended use, and you acknowledge that the failure to do so may result in serious bodily injury or death, as well as damage to the vehicle itself.

You will install any warning labels provided with the product so it may be prominently seen by yourself and all passengers. You will notify all passengers of the modifications performed to your vehicle prior to operation.

Insurance companies may handle coverage of a modified vehicle differently. Please check with your insurance carrier prior to modifying the vehicle to ensure your coverage remains sufficient.

Installation of this product(s) may void your vehicle warranty. If this is a concern, please check with the manufacturer or dealer before purchase or installation of this product(s).

HIGHLIFTER



HIGH LIFTER LIMITED LIFETIME WARRANTY

High Lifter offers a Limited Lifetime Warranty to the original purchaser that our product shall be free from defects in material and workmanship for the life of the product if utilized in accordance with the manufacturer's instructions for installation and operation of said products.

LIMITED LIFETIME WARRANTY EXTENDS TO THE FOLLOWING PRODUCT LINES:

- **Lift Kits (Signature, Standard and Big Lifts)**
- **Control Arms**
- **Trailing Arms**
- **Radiator Relocation Kits**
- **Portal Gear Lifts**
- **Wheel Spacers**
- **Tow Hooks**
- **Control Arm Link Kits**

Damages to vehicle or any other object during the installation, use, or removal of High Lifter products are not covered under this warranty. Normal wear items included with any of the products covered under this Limited Lifetime Warranty are excluded from coverage. These items include, but are not limited to heim joints, tie rods, bearings, bushings, seals, gaskets, zinc plating, painted and powder coated finishes. Other exclusions of coverage under this warranty include, but are not limited to: damage or product failure due to improper installation, lack of maintenance, product modification, abuse, collision or use on vehicles for which product was not designed, repairs performed by anyone other than approved High Lifter personnel or made using non-High Lifter components. This warranty is valid for the original purchaser only and is non-transferable. High Lifter reserves the right to inspect any product before determining if the claim is valid and covered under this warranty. Claims determined to be caused by reasons other than a manufacturer defect will be rejected and an estimate for repair or cost of a replacement product if a repair is not possible, will be provided.

This warranty is exclusive and is in lieu of any implied warranty of merchantability, fitness for a particular purpose or other warranty of quality, whether express or implied, except the warranty of title.

WARRANTY PROCESSING

If you suspect your product is defective, **DO NOT** disassemble the product to determine the cause without prior approval as it may void your warranty status. This is especially true with our Portal Gear Lift. To begin the claim process, please e-mail our warranty team at warrantycare@highlifter.com and include the following in the e-mail:

- Your full name, address and contact phone number.
- The year, make and model of your vehicle
- The part number of the product
- Photos of the product installed, and vehicle product is installed on
- Proof of Purchase (Required for all warranty claims and you must be the original purchaser)

Once a claim is created, you will receive a return authorization number (RMA). Write this number on the outside of the box containing your defective product and include it along with your name and contact information inside the box. Product must be returned in the original box or a box of equal strength and packaging. Product sent without an RMA number visible on the outside of the box or sent COD will be refused. Ship your product to the following address:

High Lifter Products

Attn: Returns 7455 Atkinson Drive, Shreveport, LA 71129

Once your product is received, we often have your replacement or repaired product shipped back to you within 3-business days of receiving it. Please note that High Lifter is not responsible for shipping charges on product returned for warranty or repair, including duties and fees required by those residing outside the United States.

**THANK YOU FOR CHOOSING
HIGHLIFTER**

PARTS

HDRB-RZRPROR-1 79-16354

UPPER RADIUS BARS 79-15233 (2 EACH)



7/8" LH HEIM
79-15323
(QTY 2)



7/8" LH JAM NUT
54-96175
(QTY 2)



7/8" HIGH
MISALIGNMENT
SPACER
79-16185
(QTY 8)



7/8" RH JAM NUT
54-60883
(QTY 2)



92W BUSHING
73-12960
(QTY 4)



7/8" RH HEIM
79-12001
(QTY 2)

HDRB-RZRPROR-SB 79-16356

LOWER RADIUS BARS 79-15235 (2 EACH)



3/4 HIGH
MISALIGNMENT
SPACER
79-16288
(QTY 4)



7/8" HIGH
MISALIGNMENT
SPACER
79-16185
(QTY 4)



92W BUSHING
73-12960
(QTY 4)



7/8" RH JAM NUT
54-60883
(QTY 2)



7/8" RH HEIM
79-12001
(QTY 2)



960 - 3/4
BEARING
73-13005
(QTY 2)



103H RETAINING
RING
73-10077
(QTY 4)


STEP 1

STOCK RADIUS BARS REMOVAL

PLACE JACK UNDER THE CENTER REAR OF THE MACHINE AND LIFT UNTIL THE WHEELS ARE OFF THE GROUND. BE CAREFUL TO SECURE PROPERLY SO IT IS STABLE ON THE JACK OR JACKSTANDS. REMOVE WHEELS.



THESE ARE THE EIGHT FACTORY BOLTS, WASHERS AND NUTS YOU WILL BE REMOVING FOR THIS INSTALL. (21MM SOCKET)



KEEP ALL FACTORY BOLTS, WASHERS AND NUTS. THEY WILL BE USED TO INSTALL THE NEW HEAVY DUTY RADIUS BARS.

THESE INSTRUCTIONS ARE STEPS FOR THE INSTALLATION OF UPPERS AND LOWERS AT THE SAME TIME. IF YOU ONLY PURCHASED ONE OR THE OTHER ONLY FOLLOW THE STEPS PERTAINING TO THAT RADIUS BAR.

STEP 2

STOCK RADIUS BARS REMOVAL

FIRST LOOSEN THE FACTORY BOLT ON THE LOWER RADIUS BAR AT THE BACK PLATE. **DO NOT REMOVE THE BOLT AT THIS TIME.** NEXT, REMOVE THE BOLT AND NUT FROM THE LOWER RADIUS BAR AT THE KNUCKLE. REPEAT STEPS FOR THE UPPER RADIUS BAR.



STEP 3

STOCK RADIUS BARS REMOVAL


NOW REMOVE BOTH FACTORY RADIUS BARS FROM THE BACK PLATE.



STEP 4

HEIM JOINTS

BEFORE YOU CAN INSTALL THE NEW HEAVY DUTY RADIUS BARS YOU WILL NEED TO INSTALL THE HIGH MISALIGNMENT BUSHINGS. INSTALL ONE BUSHING PER EACH SIDE OF EACH HEIM JOINT ON EACH RADIUS BAR.



STEP 5

INSTALLATION

INSTALL THE LOWER RADIUS BAR FIRST STARTING AT THE BACK PLATE USING THE FACTORY BOLT, WASHER AND NUT. LOOSELY TIGHTEN. NEXT, INSTALL THE OTHER END OF THE RADIUS BAR AT THE KNUCKLE USING THE FACTORY BOLT, WASHER AND NUT AND LOOSELY TIGHTEN.



STEP 6

INSTALLATION

INSTALL BOTH UPPER RADIUS BARS STARTING AT THE BACK PLATE USING THE FACTORY BOLT AND NUT. LOOSELY TIGHTEN. NEXT, INSTALL THE OTHER ENDS OF THE RADIUS BARS AT THE KNUCKLE USING THE FACTORY BOLT, WASHER AND NUT AND LOOSELY TIGHTEN.




TIP: YOU CAN USE A LONG SHAFT OR SCREW DRIVER TO HELP GET THE RADIUS BARS TO LINE UP.

STEP 7

INSTALLATION

ONCE EVERYTHING IS IN PLACE CHECK TO MAKE SURE EVERYTHING FITS CORRECTLY. THEN TIGHTEN ALL BOLTS AND NUTS TO FACTORY SPECS. REPEAT ALL STEPS ON OPPOSITE SIDE. REINSTALL WHEELS. LOWER THE JACK. FOR INSTRUCTIONS ON ADJUSTING THE CAMBER REFER TO THE BACK OF THESE INSTRUCTIONS.



Thank You For Choosing
HIGHLIFTER

ADJUSTING WHEEL CAMBER

THE DOUBLE HIEM JOINTS ON THE UPPER RADIUS BARS ALLOWS YOU TO ADJUST THE WHEEL CAMBER WHILE THE MACHINE IS SITTING ON THE GROUND.

MAKE ALL ADJUSTMENTS IN SMALL INCREMENTS WITHIN A HALF DEGREE OF 90 DEGREES ON AVERAGE. AFTER ALIGNMENT IS COMPLETE, TIGHTEN JAM NUTS AND SECURE WITH BLUE LOCTITE. REPEAT ON OPPOSITE SIDE.

NOTE: WHEN READJUSTING, LEAVE THE JAM NUTS LOOSE. DO NOT TIGHTEN UNTIL ALL FINAL ADJUSTMENTS HAVE BEEN MADE.



ROTATE THE UPPER RADIUS BAR AWAY FROM THE MACHINE TO ACHIEVE NEGATIVE CAMBER.
(MAKES THE BAR SHORTER)

ROTATE THE UPPER RADIUS BAR TOWARDS THE MACHINE TO ACHIEVE POSITIVE CAMBER.
(MAKES THE BAR LONGER)



POSITIVE CAMBER

TYPICALLY USED FOR OFF ROAD APPLICATIONS, ALLOWS FOR EASIER STEERING ON UNLEVEL TERRIAN.



CORRECT CAMBER

GOOD FOR DRAG RACING AND DRIVING ON LEVEL TERRAIN.



NEGATIVE CAMBER

USED FOR DRIFT RACING AND APPLICATIONS WHERE THE MACHINE TAKES HARD TURNS AT HIGHER SPEEDS.